



Furtun apa ISF10



Aplicații: Furtun cu rezistența mare în timp în condiții dificile de utilizare, care poate fi rulat aplatizat.

Caracteristici: Furtun destinat cu predilecție ca furtun de descărcare pentru pompe submersibile precum și furtun de mare presiune pentru apă în industrie, agricultură și minerit.

Domeniu temperatură: -35°C / +80°C

Factor de siguranță: 3,15 : 1

Tub: EPDM, negru, neted.

Întăritură: Textilă, împletită.

Înveliș exterior: EPDM, negru, rezistent la abrazivitate, ozon și climat, îmbrăcăminte impregnată.

Support tehnic live

Support tehnic 24/24

Cod	Diametru interior		Grosime perete	Diametru exterior		Presiune lucru maximă	Număr strate întăritură	Greutate (aprox.)	Lungime maximă colac
	mm	înces		mm	mm				
56313 2530	25,0	1	3,0	31,0	10	2	0,31	40	
56313 3230	32,0	1 1/4	3,0	38,0	10	2	0,44	40	
56313 3830	38,0	1 1/2	3,0	44,0	10	2	0,55	40	
56313 5130	51,0	2	3,5	58,0	10	2	0,77	40	
56313 6335	63,5	2 1/2	3,5	70,5	10	2	0,84	40	
56313 7635	76,0	3	3,5	83,0	10	2	0,90	40	
56313 9040	90,0		4,0	98,0	10	2	1,30	40	
56313 0040	102,0	4	4,0	110,0	10	2	1,46	40	
56313 0540	127,0	5	4,5	136,0	10	2	2,10	40	
56313 0645	152,0	6	4,5	161,0	10	2	2,60	40	
56313 0850	203,0	8	5,0	213,0	10	4	4,10	40	
56313 1050	254,0	10	6,0	266,0	10	4	5,65	40	
56313 1270	305,0	12	7,0	319,0	10	4	7,93	15,5	

Produse

[Cilindri pneumatice](#)
[Distribuitoare pneumatice](#)
[Fitinguri](#)
[Furtunuri pneumatice](#)
[Unitati de preparare aer](#)
[Actuatori](#)
[Scule si unelte pneumatice](#)
[Pistoale aer](#)

Despre noi

[Compania](#)
[Parteneri](#)
[Contact](#)

Contact rapid

Tel./Fax: (+4) 031.437.01.40
 E-mail: office@atsol.ro



Unavailable

This map is no longer available because was moved to the trash. Please contact owner to restore access.

© 2017 Air Tech Solutions . All rights reserved.

[Home](#) | [Catalog](#) | [Parteneri](#) | [Compania](#) | [Unitati de preparare aer](#) | [Cilindri pneumatice](#) | [Furtunuri pneumatice](#) | [Scule si unelte pneumatice](#) | [Cine suntem](#)
[Download Catalog Pneumatice 2015](#) | [Contact](#)