

## Conector rapid triplu redus cu plug-in



### Conector rapid triplu redus cu plug-in


Cuple rapide cu plug-in furtun-furtun din policarbonat.

Diametre port-furtun: Ø4, Ø6, Ø8, Ø10, Ø12.

Presiune lucru max 20 bar.

Temperatura -20°C ... +80°C

Cod: BPKGJ



Diametru (ØD1)	Diametru (ØD)		
	4	6	8
6	BPKGJ64	-	-
8	BPKGJ84	BPKGJ86	-
10	-	BPKGJ106	BPKGJ108

Produse

Cilindri pneumatici

Despre noi

Compania

Contact rapid

Tel./Fax: (+4) 031.437.01.40

Support tehnic live

Support tehnic 24/24

[Distribuitoare pneumatice](#)

[Parteneri](#)

[Fitinguri](#)

[Contact](#)

[Furtunuri pneumatice](#)

[Unitati de preparare aer](#)

[Actuatori](#)

[Scule si unelte pneumatice](#)

[Pistoale aer](#)

E-mail: [office@atsol.ro](mailto:office@atsol.ro)



**404.** That's an error.

The requested URL was not found on this server. That's all we know.

© 2017 Air Tech Solutions . All rights reserved.

[Home](#) | [Catalog](#) | [Parteneri](#) | [Compania](#) | [Unitati de preparare aer](#) | [Cilindri pneumatice](#) | [Furtunuri pneumatice](#) | [Scule si unelte pneumatice](#) | [Cine suntem](#)  
[Download Catalog Pneumatice 2015](#) | [Contact](#)