



Reductie rapida Y Furtun plugin



Cuple rapide pentru furtun pneumatic Y din policarbonat.

Diametre port-furtun: Ø4, Ø6, Ø8, Ø10, Ø12.


Presiune lucru max 20 bar.

Temperatura -20°C ... +80°C

Cod: BPYGJ



Diametru (ØD1)	Diametru (ØD)			
	4	6	8	10
6	BPYGJ64	-	-	-
8	BPYGJ84	BPYGJ86	-	-
10	-	BPYGJ106	BPYGJ108	-
12	-	BPYGJ126	BPYGJ128	BPYGJ1210



Produce

Cilindri pneumatici

Distribuitoare pneumatice

Fitinguri

Despre noi

Compania

Parteneri

Contact

Contact rapid

Tel./Fax: (+4) 031.437.01.40

E-mail: office@atsol.ro

Offline

[Furtunuri pneumatice](#)
[Unitati de preparare aer](#)
[Actuatori](#)
[Scule si unelte pneumatice](#)
[Pistoale aer](#)



404. That's an error.

The requested URL was not found on this server. That's all we know.

© 2017 Air Tech Solutions . All rights reserved.

[Home](#) | [Catalog](#) | [Parteneri](#) | [Compania](#) | [Unitati de preparare aer](#) | [Cilindri pneumatice](#) | [Furtunuri pneumatice](#) | [Scule si unelte pneumatice](#) | [Cine suntem](#)
| [Download Catalog Pneumatice 2015](#) | [Contact](#)